

SIEMENS SIMATIC S7-200 PLC 6ES7223-1BF22-0XA8 EM 223 24 VDC Digital Comb 4 Inputs/4 Outputs

Our Product Introduction

Basic Information

- Place of Origin: Germany
- Brand Name: SIEMNENS
- Certification: CE
- Model Number: 6ES7223-1BF22-0XA8
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 20*20*10
- Delivery Time: 7-14 DAYS
- Payment Terms: L/C, T/T
- Supply Ability: 100PS



Product Specification

- Operating Voltage: 24 V DC
- Dimensions: 290 X 100 X 120 Mm
- Memory: 256 KB
- Operating Temperature: 0-60°C
- Number Of Digital Inputs: 16
- Number Of Analog Outputs: 4
- Number Of Digital Outputs: 16
- Weight: 1.2 Kg
- Cpu Type: 315-2DP
- Number Of Analog Inputs: 8
- Product Type: Programmable Logic Controller (PLC)

for more products please visit us on plcsimatic.com

Product Description

SIEMENS SIMATIC S7-200 PLC 6ES7223-1BF22-0XA8 EM 223 24 VDC Digital Comb 4 Inputs/4 Outputs

Product Introduction:

The SIEMENS SIMATIC S7-200 PLC 6ES7223-1BF22-0XA8 is an EM 223 digital combination module designed for the SIEMENS SIMATIC S7-200 PLC series. This module combines 4 digital input and 4 digital output channels, all operating at a voltage level of 24V DC.

Product Information and Specifications:

- Model: SIMATIC S7-200 PLC 6ES7223-1BF22-0XA8
- Module Type: EM 223 Digital Combination
- Number of Digital Inputs: 4
- Number of Digital Outputs: 4
- Input/Output Voltage: 24V DC

Product Attributes:

- Model: SIMATIC S7-200 PLC 6ES7223-1BF22-0XA8
- Module Type: EM 223 Digital Combination
- Number of Digital Inputs: 4
- Number of Digital Outputs: 4
- Input/Output Voltage: 24V DC

The SIMATIC S7-200 PLC 6ES7223-1BF22-0XA8 module is a digital combination module designed for the SIEMENS SIMATIC S7-200 PLC series. It integrates 4 digital input and 4 digital output channels into a single module, providing a compact solution for controlling and monitoring digital signals.

The 4 digital input channels allow for monitoring the status of external devices or sensors, while the 4 digital output channels enable the control of connected devices or actuators.

All input and output channels operate at a voltage level of 24V DC, making it compatible with devices and systems utilizing this voltage standard.

The SIMATIC S7-200 PLC 6ES7223-1BF22-0XA8 module is suitable for applications where a combination of digital inputs and outputs is required, such as in small-scale automation projects or control systems.

For detailed information on installation, wiring, and configuration of the SIMATIC S7-200 PLC 6ES7223-1BF22-0XA8 digital combination module, it is recommended to refer to the product documentation provided by Siemens or contact their technical support. They can provide specific guidance on integrating the module into the PLC system, configuring the input and output channels, and assist with any inquiries related to its specifications and attributes.



Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen