

3RW3036-2BB14 Ac Semiconductor Motor Starter Siemens SIRIUS S2 45A 22kW

Our Product Introduction

Basic Information

- Place of Origin: Germany
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 3RW3036-2BB14
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 15,10 x 15,40 x 4,60
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100



Product Specification

- Communication Protocols: Modbus TCP, Ethernet/IP, DeviceNet
- Ambient_Temperature_Range: -10 To 50 Degrees Celsius
- Communication_Interfaces: PROFIBUS, PROFINET, Modbus RTU
- Motor_Power_Range: 1.5-560kW
- Protection_Functions: Overload, Phase Failure, Phase Sequence, Underload
- Product_Name: SIRIUS 3RW Soft Starters
- Product_Type: Soft Starter
- Enclosure_Rating: IP20
- Certifications: CE, UL, CUL, CCC, EAC
- Display: LCD
- Control_Voltage: 24V DC
- Current_Rating: 3-1050A
- Operating_Modes: Soft Start, Soft Stop, Pump Control, Energy Saving
- Programming_Software: SIRIUS Soft Starter FC

for more products please visit us on plcsimatic.com

Product Description

SIEMENS 3RW3036-2BB14 SIRIUS soft starter S2 45 A, 22 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC spring-type terminal

The SIEMENS 3RW3036-2BB14 SIRIUS Soft Starter S2 is a motor control device used for starting and controlling the speed of three-phase induction motors. Here are the details about the SIEMENS 3RW3036-2BB14 SIRIUS Soft Starter S2:

1. Model: The 3RW3036-2BB14 is a specific model of the SIRIUS Soft Starter S2 series.
2. Current Rating: The soft starter has a current rating of 45 A, which means it can handle motors with a maximum current draw of 45 Amperes.
3. Power Rating: The soft starter is designed for motors with a power rating of 22 kW at 400 V AC. This means it can control motors up to 22 kilowatts of power.
4. Voltage Range: The soft starter supports a voltage range of 200-480 V AC for the main supply. Additionally, it requires a control voltage of 110-230 V AC or DC.
5. Terminal Type: The soft starter features spring-type terminals for easy and secure connection of electrical wiring.

The SIEMENS 3RW3036-2BB14 SIRIUS Soft Starter S2 is commonly used in industrial applications to smoothly start and control the speed of motors, reducing mechanical stress and preventing high inrush currents. It offers protection features such as motor overload protection, phase asymmetry detection, and phase failure protection.

Please note that the temperature rating you mentioned (40 °C) indicates the maximum ambient temperature at which the soft starter can operate effectively.

For more detailed specifications, installation guidelines, and specific information about the SIEMENS 3RW3036-2BB14 SIRIUS Soft Starter S2, it is recommended to refer to the official documentation provided by Siemens or contact their technical support for accurate and up-to-date information based on your requirements.

Product	
Article Number (Market Facing Number)	3RW3036-2BB14
Product Description	SIRIUS soft starter S2 45 A, 22 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC spring-type terminals
Product family	3RW30 soft starters
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Region Specific PriceGroup / Headquarter Price Group	42G / 42G
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Materials	None
Metal Factor	LBO-----
Delivery information	
Export Control Regulations	AL : N / ECCN : N
Estimated dispatch time (Working Days)	3 Day/Days
Net Weight (kg)	1,159 Kg
Packaging Dimension	70,00 x 170,00 x 198,00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4011209719330
UPC	754554958514
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	5345
Group Code	R711
Country of origin	Czech Republic



Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen