## Allen Bradley 1769-L32E CompactLogix 750KB Enet Controller

## **Basic Information**

Place of Origin: GermanyBrand Name: Allen Bradley

Certification:

Model Number: 1769-L32E

Minimum Order Quantity: 1Price: USD

• Packaging Details: 15,10 x 15,40 x 4,60

Delivery Time: 10-12Days
Payment Terms: L/C, T/T
Supply Ability: 100



## **Product Specification**

Processor: Intel Celeron M 1 GHz

Operating System: Windows CEWeight: 1.5 Lbs

Storage Temperature: -20-70 Degrees Celsius
 Communication Ports: Ethernet, USB, Serial
 Certifications: UL, CUL, CE, C-Tick, KCC

Display Type: TFT Color Display
Dimensions: 6.5 X 8.5 X 2.5 Inches

Display Size: 6 InchesInput Voltage: 18-30V DC

• Software Compatibility: FactoryTalk View Studio, FactoryTalk View

ME, FactoryTalk ViewPoint

• Touchscreen: Yes

• Operating Temperature: 0-55 Degrees Celsius

Memory: 512 MB RAM, 512 MB Flash

## **Product Description**

Allen Bradley 1769-L32E CompactLogix 750KB Enet Controller

Okay, let's take a closer look at the Allen-Bradley 1769-L32E CompactLogix 750KB Ethernet Controller:

- 1. Product Name:
- Allen-Bradley 1769-L32E CompactLogix 750KB Ethernet Controller
- 2. Description:
- The 1769-L32E is a compact programmable automation controller (PAC) from the Allen-Bradley CompactLogix series.
- It serves as the central control unit for the CompactLogix control system, providing logic processing, communication, and networking capabilities.
- 3. Key Features:
- 750KB of user memory
- Integrated Ethernet port for communication and networking
- Supports up to 16 local and remote I/O modules
- Configurable using the Studio 5000 Logix Designer software
- 4. Applications:
- The 1769-L32E CompactLogix controller is commonly used in a variety of industrial automation and control applications, such as:
- Machine control
- Process control
- Material handling
- Building automation systems
- 5. Connectivity:
- The 1769-L32E provides the following connectivity options:
- Ethernet port for communication and networking
- Backplane connection to the CompactLogix I/O modules
- Serial communication ports (optional)
- 6. Capabilities:
- 750KB of user memory for storing program logic and data
- Integrated Ethernet port for communication and networking
- Supports up to 16 local and remote I/O modules
- Configurable using the Studio 5000 Logix Designer software
- 7. Compatibility:
- The 1769-L32E CompactLogix 750KB Ethernet Controller is designed to be compatible with the Allen-Bradley CompactLogix PAC system.
- It can be installed in the CompactLogix chassis, providing the central control and communication functionality for the control system.
- The controller is supported by the Studio 5000 Logix Designer software, which is used to program, configure, and monitor CompactLogix-based control systems.

The Allen-Bradley 1769-L32E CompactLogix 750KB Ethernet Controller is a powerful and versatile control unit within the CompactLogix family. Its 750KB of user memory, integrated Ethernet connectivity, and support for up to 16 I/O modules make it a suitable choice for a wide range of industrial automation and control applications. The controller's seamless integration with the Studio 5000 Logix Designer software further enhances its programming, configuration, and monitoring capabilities within the CompactLogix control system.

If you have any additional questions or need more information about the 1769-L32E CompactLogix 750KB Ethernet Controller, please feel free to ask.





**VOBOAL** Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen