

SIEMENS 6ES7972-0BB52-0XA0 MBIT/S 90° CABLE OUTLET, INSULATION DISPLACEMENT METHOD FASTCONNECT, WITH PG RECEPTACLE

Basic Information

- Place of Origin: Germany
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 6ES7972-0BB52-0XA0
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 15,10 x 15,40 x 4,60
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100



Product Specification

- Processor: ARM Cortex-A8 600 MHz
- Storage: 128 MB Flash
- Display Size: 7 Inches
- Expansion Slots: 1 X SD Card Slot
- Certifications: CE, UL, CSA, FCC
- Dimensions: 200 X 150 X 40 Mm
- Operating System: Windows Embedded Compact 7
- Operating Temperature: 0-50°C
- Power Supply: 24 V DC
- Memory: 256 MB RAM
- Touchscreen: Yes
- Communication Ports: 2 X Ethernet, 2 X USB, 1 X RS232/485
- Resolution: 800 X 480 Pixels
- Weight: 0.8 Kg

Product Description

SIEMENS 6ES7972-0BB52-0XA0 MBIT/S 90° CABLE OUTLET, INSULATION DISPLACEMENT METHOD FASTCONNECT, WITH PG RECEPTACLE

The Siemens 6ES7972-0BB52-0XA0 is a PROFIBUS DP (Decentralized Peripherals) cable with a 90° cable outlet and insulation displacement method FastConnect. It also features a PG receptacle. Here's some information about this product:

1. Manufacturer: Siemens
 2. Model: 6ES7972-0BB52-0XA0
 3. Cable Type: This is a PROFIBUS DP cable, which is commonly used for communication between industrial devices and controllers in automation systems.
 4. Cable Outlet: The cable has a 90° cable outlet, which means it is designed to make a right angle bend at the connector end. This can be useful for installations where space is limited or to ensure proper cable routing.
 5. Insulation Displacement Method: The cable utilizes the insulation displacement method for termination. This method allows for easy and reliable connection by displacing the insulation of the wires to establish electrical contact.
 6. FastConnect: The cable features the FastConnect system, which is Siemens' proprietary technology for quick and tool-free assembly of PROFIBUS cables. This simplifies the installation process and reduces setup time.
 7. PG Receptacle: The cable is equipped with a PG (Panzer-Gewinde) receptacle. PG threads are commonly used in industrial applications for cable glands and connectors, providing a secure and reliable connection.
- For detailed specifications, technical data, and compatibility information specific to the Siemens 6ES7972-0BB52-0XA0 PROFIBUS DP cable, it is best to refer to the official documentation provided by Siemens or contact their technical support. They will be able to provide you with accurate and up-to-date information based on your specific requirements and the latest product information available.

Product	
Article Number (Market Facing Number)	6ES7972-0BB52-0XA0
Product Description	SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s 90° cable outlet, Insulation displacement method FastConnect, With PG receptacle 15.8x 59x 35.6 mm (BxHxD)
Product family	RS485 bus connector
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Region Specific PriceGroup / Headquarter Price Group	250 / 250
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Materials	None
Metal Factor	None
Delivery information	
Export Control Regulations	AL : N / ECCN : N
Estimated dispatch time (Working Days)	1 Day/Days
Net Weight (kg)	0,047 Kg
Packaging Dimension	6,80 x 7,90 x 3,20
Package size unit of measure	CM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4025515077305
UPC	662643406184
Commodity Code	85366990
LKZ_FDB/ CatalogID	ST76
Product Group	4059
Group Code	R151
Country of origin	Germany



Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen