

SIEMENS 6EP1336-1LB00 SITOP PSU100L 24 V/20 A STABILIZED POWER SUPPLY INPUT: 100-240 V AC OUTPUT: 24 V DC/20 A

Basic Information

- Place of Origin: China
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 6EP1336-1LB00
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 163,00 x 190,00 x 143,00 mm
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100PS



Product Specification

- Communication Interface: RS-485
- Warranty: 2 Years
- Input Voltage Range: 85-264 V AC, 90-375 V DC
- Model: 6EP1334-1LB00
- Safety Standards: EN/IEC 60950-1
- Number Of Outputs: 1
- Protection Class: IP20
- Output Current: 20 A
- Product Type: Power Supply
- Cooling Method: Convection
- Additional Features: Overload And Short-circuit Protection
- Mounting Type: DIN Rail
- Dimensions: 163,00 X 190,00 X 143,00 Mm
- Certifications: CE, UL, CUL, ATEX, FM, CFM
- Type: Switch Mode Power Supply

Product Description

SIEMENS 6EP1336-1LB00 SITOP PSU100L 24 V/20 A STABILIZED POWER SUPPLY INPUT: 100-240 V AC OUTPUT: 24 V DC/20 A

Here are the key details on the Siemens 6EP1336-1LB00 SITOP PSU100L 24 V/20 A stabilized power supply:

1. Product Overview:

- The Siemens 6EP1336-1LB00 is a SITOP PSU100L stabilized power supply.
- It provides a regulated 24 V DC output at 20 A for industrial applications.

2. Key Features:

- Input Voltage: 100-240 V AC
- Output Voltage: 24 V DC
- Output Current: 20 A
- Stabilized and regulated DC output

3. Technical Specifications:

- Input Voltage: 100-240 V AC, 47-63 Hz
- Input Current: 8 A (at 120 V AC), 4 A (at 230 V AC)
- Output Voltage: 24 V DC
- Output Current: 20 A
- Output Power: 480 W
- Efficiency: Typically 94%
- Dimensions (W x H x D): Compact design for space-saving installation
- Mounting: DIN rail mounting

4. Functionality and Applications:

- The SITOP PSU100L 24 V/20 A power supply provides a stable and regulated 24 V DC output.
- It is designed for use in a wide range of industrial automation and control applications, including PLC systems, drives, and other equipment that require high-power 24 V DC supplies.
- The wide input voltage range of 100-240 V AC allows the power supply to be used globally, making it versatile for international applications.

5. Integration and Configuration:

- The Siemens 6EP1336-1LB00 SITOP PSU100L 24 V/20 A power supply is designed for easy integration into industrial control systems.
- It mounts on a DIN rail, allowing for flexible installation in control cabinets and other enclosures.
- The power supply connects directly to the AC input and provides the regulated 24 V DC output to the connected devices.
- Configuration and setup of the SITOP PSU100L 24 V/20 A power supply are typically done as part of the overall system design and commissioning process.

6. Advantages:

- Provides a stable and regulated 24 V DC output up to 20 A
- Wide input voltage range of 100-240 V AC for global use
- Compact, DIN rail-mounted design for space-saving installation
- Efficient power conversion with typically 94% efficiency
- Suitable for high-power industrial automation and control applications
- Enhances the reliability and performance of industrial systems

7. Certifications and Approvals:

- The Siemens 6EP1336-1LB00 SITOP PSU100L 24 V/20 A power supply is designed to meet relevant safety and quality standards for industrial applications.
- Additional certifications may be available based on specific regional or application requirements.

Please let me know if you need any further details on this Siemens SITOP PSU100L 24 V/20 A stabilized power supply.

Product	
Article Number	6EP1336-1LB00
Product Description	SITOP PSU100L 24 V/20 A Stabilized power supply input: 100-240 V AC output: 24 V DC/20 A
Product family	1-phase, 24 V DC
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	583
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	see also metal factor (further details are available on the help page)
Delivery information	
Export Control Regulations	AL : N / ECCN : EAR99
Estimated dispatch time (Working Days)	1 Day(s)
Net Weight (kg)	1,800 Kg
Packaging Dimension	163,00 x 190,00 x 143,00

Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4025515154549
UPC	804766459504
Commodity Code	85044083
LKZ_FDB/ CatalogID	KT10-PH
Product Group	4219
Group Code	R315
Country of origin	China



VOBOAL Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen