

SIEMENS 3RW3014-2BB04 SIRIUS SOFT STARTER S00 6.5 A, 3 KW/400 V, 40 °C 200-480 V AC, 24 V AC/DC SPRING-TYPE TERMINALS

Basic Information

- Place of Origin: Czech Republic
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 3RW3014-2BB04
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 57,00 x 125,00 x 165,00MM
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100PS



Product Specification

- Enclosure Rating: IP20/IP54
- Stop Function: Coast To Stop
- Integrated Pump Control: Yes
- Communication: PROFIBUS, PROFINET, Modbus RTU
- Protection Rating: IP20
- Communication Interfaces: PROFIBUS, PROFINET, Modbus RTU, Modbus TCP
- Communication Interface: Modbus RTU
- Soft Start Time: 0.1-20 Seconds
- Integrated Bypass: Yes
- Warranty: 2 Years
- Soft Start Function: Ramp-up, Kickstart, Current Limitation
- Product Type: Soft Starter
- Starting Method: Soft Start
- Soft Stop: Ramp-down Time

Product Description

SIEMENS 3RW3014-2BB04 SIRIUS SOFT STARTER S00 6.5 A, 3 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC SPRING-TYPE TERMINALS

Here are the key details on the Siemens 3RW3014-2BB04 SIRIUS Soft Starter S00 6.5A:

Product Details:

- Model Number: 3RW3014-2BB04
- Product Name: SIRIUS Soft Starter S00 6.5A

Description:

The Siemens 3RW3014-2BB04 is a SIRIUS Soft Starter S00 model with a rated current of 6.5A. It is designed to provide smooth, controlled starting and stopping of three-phase AC motors.

Key Features:

- Rated current: 6.5A
- Rated power: 3 kW at 400V AC, 40°C
- Input voltage range: 200-480V AC
- Control voltage: 24V AC/DC
- Spring-type terminals for connections
- Compact, space-saving design
- Integrated overload protection
- Configurable ramp-up and ramp-down times
- Built-in bypass contactor

Detailed Specifications:

- Rated Operational Current: 6.5A
- Rated Power: 3 kW at 400V AC, 40°C
- Input Voltage Range: 200-480V AC, 3-phase
- Control Voltage: 24V AC/DC
- Dimensions (W x H x D): 45 x 100 x 150 mm
- Mounting: Screw mounting
- Connections: Spring-type terminals
- Overload Protection: Integrated
- Ramp-up/Ramp-down Time: Configurable
- Bypass Contactor: Integrated

The Siemens 3RW3014-2BB04 SIRIUS Soft Starter S00 6.5A is a compact and versatile soft starter designed for the smooth and controlled starting and stopping of three-phase AC motors. It is suitable for a wide range of applications, such as:

- Pump and fan applications
- Compressor applications
- Conveyor systems
- HVAC equipment
- Other small to medium-sized industrial machinery

The soft starter helps to reduce mechanical and electrical stresses on the motor during start-up and shut-down, prolonging the motor's lifespan and improving overall system efficiency. Its compact design and spring-type terminal connections make it easy to integrate into various industrial control systems.

Please note that proper selection, installation, and configuration of the soft starter is important to ensure its optimal performance and compatibility with the specific motor and application. It is recommended to consult with Siemens or a qualified electrical engineer for guidance on the selection and use of this soft starter model.

Product	
Article Number	3RW3014-2BB04
Product Description	SIRIUS soft starter S00 6.5 A, 3 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC Spring-type terminals
Product family	3RW30 soft starters
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	42G
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	LBO-----
Delivery information	
Export Control Regulations	AL : N / ECCN : EAR99
Estimated dispatch time (Working Days)	3 Day(s)
Net Weight (kg)	0,466 Kg
Packaging Dimension	57,00 x 125,00 x 165,00
Package size unit of measure	MM
Quantity Unit	1 Piece

Packaging Quantity	1
Additional Product Information	
EAN	4011209719675
UPC	754554958187
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	5345
Group Code	R711
Country of origin	Czech Republic



Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen