SIEMENS 3RW3018-2BB04 SIRIUS SOFT STARTER S00 17.6 A, 7.5 KW/400 V, 40 °C 200-480 V AC, 24 V AC/DC SPRING-TYPE TERMINALS

Basic Information

VOBOAL

Place of Origin: Czech Republic
 Brand Name: SIEMENS
 Certification: CE

Model Number: 3RW3018-2BB04

Minimum Order Quantity: 1Price: USD

• Packaging Details: 123,00 x 162,00 x 60,00MM

Delivery Time: 10-12Days
Payment Terms: L/C, T/T
Supply Ability: 100PS



Product Specification

Soft Start Function: Ramp-up, Kickstart, Current Limitation

Motor Power Range: 1.5-560kW
 Stop Function: Coast To Stop
 Model: 3RW Soft Starters
 Soft Stop Time: 0.1-20 Seconds

Warranty: 2 YearsStarting Torque: AdjustableMounting Type: DIN Rail

• Ambient Temperature: -10 To 40 Degrees Celsius

Ambient Temperature

Range:

-10°C To +40°C

Rated Voltage: 200-690VVoltage Range: 200-690V

• Motor Control: Soft Start, Soft Stop, Pump Control

Integrated Bypass: Yes

Product Description

SIEMENS 3RW3018-2BB04 SIRIUS SOFT STARTER S00 17.6 A, 7.5 KW/400 V, 40 °C 200-480 V AC, 24 V AC/DC SPRING-TYPE TERMINALS

Here are the key details on the Siemens 3RW3018-2BB04 SIRIUS Soft Starter S00 17.6A:

Product Details:

- Model Number: 3RW3018-2BB04

- Product Name: SIRIUS Soft Starter S00 17.6A

Description:

The Siemens 3RW3018-2BB04 is a SIRIUS Soft Starter S00 model with a rated current of 17.6A. It is designed to provide smooth, controlled starting and stopping of three-phase AC motors.

Key Features:

- Rated current: 17.6A

- Rated power: 7.5 kW at 400V AC, 40°C - Input voltage range: 200-480V AC

- Control voltage: 24V AC/DC

- Spring-type terminals for connections
- Compact, space-saving design
- Integrated overload protection
- Configurable ramp-up and ramp-down times
- Built-in bypass contactor

Detailed Specifications:

- Rated Operational Current: 17.6A
- Rated Power: 7.5 kW at 400V AC, 40°C
- Input Voltage Range: 200-480V AC, 3-phase
- Control Voltage: 24V AC/DC
- Dimensions (W x H x D): 45 x 100 x 190 mm
- Mounting: Screw mounting
- Connections: Spring-type terminals
- Overload Protection: Integrated
- Ramp-up/Ramp-down Time: Configurable
- Bypass Contactor: Integrated

The Siemens 3RW3018-2BB04 SIRIUS Soft Starter S00 17.6A is a compact and versatile soft starter designed for the smooth and controlled starting and stopping of three-phase AC motors. It is suitable for a wide range of applications, such as:

- Pump and fan applications
- Compressor applications
- Conveyor systems
- HVAC equipment
- Other medium-sized industrial machinery

The soft starter helps to reduce mechanical and electrical stresses on the motor during start-up and shut-down, prolonging the motor's lifespan and improving overall system efficiency. Its compact design and spring-type terminal connections make it easy to integrate into various industrial control systems.

Please note that proper selection, installation, and configuration of the soft starter is important to ensure its optimal performance and compatibility with the specific motor and application. It is recommended to consult with Siemens or a qualified electrical engineer for guidance on the selection and use of this soft starter model.

Product		
Article Number	3RW3018-2BB04	
Product Description	SIRIUS soft starter S00 17.6 A, 7.5 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC Spring-type terminals	
Product family	3RW30 soft starters	
Product Lifecycle (PLM)	PM300:Active Product	
Price data		
Price Group	42G	
List Price	Show prices	
Customer Price	Show prices	
Surcharge for Raw Material	see also metal factor (further details are available on the help page)	
Metal Factor	LBO	
Delivery information		
Export Control Regulations	AL:N/ECCN:N	
Estimated dispatch time (Working Days)	3 Day(s)	
Net Weight (kg)	0,466 Kg	
Packaging Dimension	123,00 x 162,00 x 60,00	
Package size unit of measure	ММ	
Quantity Unit	1 Piece	

Packaging Quantity	[1	
Additional Product Information		
EAN	4011209719743	
UPC	754554958217	
Commodity Code	85371098	
LKZ_FDB/ CatalogID	CC-IC10	
Product Group	5345	
Group Code	R711	
Country of origin	Czech Republic	



VOBOAL Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017





Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen