

Germany

SIEMENS

6ES7314-6CG03-0AB0

13,40 x 15,20 x 12,40CM

CE

1 USD

100PS

## SIEMENS 6ES7314-6CG03-0AB0 SIMATIC S7-300 CPU314C-2 DP CONTROLLER, MPI/DP, 96KB FRONT CONNECTOR (2X 40-POLE)

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability:



## **Product Specification**

<ul> <li>Operating Voltage:</li> </ul>	24V DC
• Number Of Digital Outputs:	32
<ul> <li>Mounting Options:</li> </ul>	Panel Or VESA Mount
Certifications:	CE, UL, CSA
<ul> <li>Display Size:</li> </ul>	7 Inch
Number Of Analog Inputs:	8
• Touchscreen:	Yes
Communication Ports:	Ethernet, USB, RS232/485
Number Of Communication     Ports:	2
<ul> <li>Programming Language:</li> </ul>	Ladder Logic
<ul> <li>Software Compatibility:</li> </ul>	STEP 7, TIA Portal
Memory Size:	128 KB
Communication Protocols:	PROFINET, PROFIBUS

• Communication Interfaces: MPI/PROFIBUS DP

## **Product Description**

SIEMENS 6ES7314-6CG03-0AB0 SIMATIC S7-300 CPU314C-2 DP CONTROLLER, MPI/DP, 96KB FRONT CONNECTOR (2X 40-POLE)

The \*\*SIEMENS 6ES7314-6CG03-0AB0 SIMATIC S7-300 CPU314C-2 DP CONTROLLER\*\* is a controller unit with the following specifications:

- \*\*Model\*\*: CPU314C-2 DP

- \*\*Interfaces\*\*: MPI/DP - \*\*Memory\*\*: 96KB - \*\*Front Connector\*\*: 2x 40-pole

This controller is part of the SIMATIC S7-300 series and is equipped with MPI/DP interfaces for communication, 96KB of memory for program storage and execution, and features a front connector with 2x 40-pole connectors for connecting to external devices or modules. It is designed for industrial automation applications and offers robust performance and connectivity options for control and monitoring tasks.

Product					
Article	Article				
Number	6ES7314-6CG03-0AB0				
Product	***Spare part*** SIMATIC S7-300, CPU 314C-2 DP Compact CPU with MPI, 24				
Descriptio	DI/16 DO, 4 AI, 2 AO, 1 Pt100, 4 high-speed counters (60 kHz), integrated DP				
n	interface, Integr. power supply 24 V DC, Work memory 96 KB, Front connector (2x 40-pole) and Micro Memory Card required				
Product					
family	Not available				
Product					
Lifecycle	PM490:Start of final year of support				
(PLM)					
PLM					
Effective	Product discontinued since: 01.10.2022				
Date					
Nietee	Product is no longer available. Successor:				
Notes	6ES7314-6CH04-0AB0 Compare Products				
Successor	information				
	6ES7314-6CH04-0AB0				
	SIMATIC S7-300, CPU 314C-2 DP Compact CPU with MPI, 24 DI/16 DO, 4 AI,				
Successor Descriptio	2 AO, 1 Pt100, 4 high-speed counters (60 kHz), integrated DP interface, Integr.				
	power supply 24 V DC, work memory 192 KB, Front connector (2x 40-pole) and				
n	Micro Memory Card required				
Price data					
Price	S20				
Group	520				
List Price	Show prices				
Customer	Show prices				
Price	Show prices				
Surcharge					
	see also metal factor (further details are available on the help page)				
Material					
Metal	see also metal factor (further details are available on the help page)				
Factor					
Delivery information					
Export					
Control	ECCN : N / AL : N				
Regulation					
o Fotimatad					
Estimated dispatch					
time	1 Day(s)				
(Working					
Davs)					
Net Weight	0.700 //				
(kg)	u,/30 kg				
Deekeeine	12 40 × 15 20 × 12 40				
Dimension	13,40 x 15,20 x 12,40				
Package					
size unit of	СМ				
measure					
Quantity	1 Piece				
Unit					
Packaging	1				
Quantity	·				
	Product Information				
	4025515074496				
UPC	Not available				
Commodit	85371091				
y Code					
r					

LKZ_FDB/ CatalogID	ST9-E5
Product Group	4256
Code	R132
Country of origin	Germany



**VOBOAL** Shenzhen Voboal Industrial Automation Co., Ltd.

€ +8613760462017 Sale@voboal.com

om 📀 plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen