SIEMENS 6ES7315-2AF00-0AB0 SIMATIC S7-300, CPU 315 CPU WITH INTEGRATED 24 V DC POWER SUPPLY, 48 KBYTES, 16KAW, 0.3MS/KAW

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details: 13,30 x 15,10 x 9,30CM

Germany

SIEMENS

6ES7315-2AF00-0AB0

CE

1 USD

100PS

- Delivery Time:
- 10-12Days • Payment Terms: L/C, T/T
- Supply Ability:



Product Specification

| • Model: | S7-300 |
|--|--------------------------------------|
| Resolution: | 800x480 Pixels |
| Power Supply: | 24 V DC |
| Memory: | 1GB - 4GB |
| Software: | SIMATIC WinCC Runtime Advanced |
| Touchscreen: | Yes |
| Communication Protocols: | PROFIBUS, MPI |
| Expansion Slots: | 1 X SD Card Slot |
| Communication Ports: | Ethernet, USB, RS232/485 |
| Display Size: | 7 Inches |
| Operating Voltage: | 24 V DC |
| Communication Interface: | PROFINET, PROFIBUS DP |
| Temperature Range: | -20°C To 60°C |
| Dimensions: | 13,30 X 15,10 X 9,30CM |
| Communication Interfaces: | MPI/DP, PROFIBUS, PROFINET, Ethernet |

Product Description

SIEMENS 6ES7315-2AF00-0AB0 SIMATIC S7-300, CPU 315 CPU WITH INTEGRATED 24 V DC POWER SUPPLY, 48 KBYTES, 16KAW, 0.3MS/KAW

The **SIEMENS 6ES7315-2AF00-0AB0 SIMATIC S7-300 CPU 315** is a CPU unit with an integrated 24 V DC power supply and the following specifications:

- **Memory:** 48 Kbytes
- **Integrated Power Supply Voltage:** 24 V DC
- **Maximum KW per memory:** 16 KW **Memory Cycle Time:** 0.3 milliseconds per KW

This CPU unit is designed for industrial automation applications, featuring 48 Kbytes of memory, an integrated 24 V DC power supply, and the capability to handle up to 16 KW of memory. With a memory cycle time of 0.3 milliseconds per KW, it provides reliable performance for controlling and managing processes in industrial settings.

| Product | | |
|---------------------------------|--|--|
| | | |
| Article Number | 6ES7315-2AF00-0AB0 | |
| Product | SIMATIC S7-300, CPU 315 CPU WITH INTEGRATED 24 V DC POWER SUPPLY, 48 KBYTES, 16KAW, 0.3MS/KAW, CLOCK, 2ND | |
| Description | INTERFACE MASTER | |
| Product family | Not available | |
| Product Lifecycle | PM500:Discontinued Product or end of PLM & Support | |
| (PLM) | | |
| PLM Effective Date | End of product lifecycle since: 01.10.2011 | |
| Notes | Product was deleted without replacement. If you need assistance please contact our local Siemens office | |
| Price data | | |
| Price Group | 2AP | |
| List Price | Show prices | |
| Customer Price | Show prices | |
| Surcharge for Raw Material | see also metal factor (further details are available on the help page) | |
| Metal Factor | see also metal factor (further details are available on the help page) | |
| Delivery information | Dn | |
| Export Control Regulations | ECCN : EAR99H / AL : N | |
| Estimated dispatch time | 1 Day(s) | |
| (Working Days) | | |
| Net Weight (kg) | 0,666 Kg | |
| Packaging Dimension | 13,30 x 15,10 x 9,30 | |
| Package size unit of measure | СМ | |
| Quantity Unit | 0 Piece | |
| Packaging Quantity | 1 | |
| Additional Product | Information | |
| EAN | 4025515060628 | |
| UPC | Not available | |
| Commodity Code | 85371091 | |
| LKZ_FDB/ CatalogID | ST9-E5 | |
| Product Group | 4302 | |
| Group Code | R111 | |
| Country of origin | Germany | |
| | | |

| SIEWIENS | CPU315-2 DP F DP USF | |
|--|----------------------------|--|
| RUN-P RUN STOP MRES | F | |
| SIMATIC S7-300 | | |
| 2 215-24F00-0480 | <u> <u>X 4</u></u> | |
| VOBOAL Shenzhen Voboal Industrial Automation Co., Ltd. | | |
| VOBOAL Shenzhen Voboal Industrial Automation Co., Ltd. Image: Constraint of the state of the s | | |