SIEMENS 3RW3017-1BB14 SIRIUS SOFT STARTER S00 12.5 A, 5.5 KW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC SCREW TERMINALS

Basic Information

Place of Origin: Czech Republic
 Brand Name: SIEMENS
 Certification: CE

Model Number: 3RW3017-1BB14

Minimum Order Quantity: 1Price: USD

• Packaging Details: 210,00 x 163,00 x 60,00MM

Delivery Time: 10-12Days
Payment Terms: L/C, T/T
Supply Ability: 100



Product Specification

• Output Current: 5A

• Starting Voltage: Adjustable From 20-100%

Motor Power Range: 0.37-55kW

Motor Voltage Ramp: Linear Or S-curve

Control Voltage: 24 V DC
Voltage: Up To 690V
Ramp-Up Time: 0-30 Seconds
Soft Stop Time: 0.1-20 Seconds

Motor Load Monitoring: YesPower Range: 3-250kW

Additional Features: Overload And Short Circuit Protection

• Programming Options: Keypad, PC Software

Rated Operational Current: 3-1050 A
Input Voltage: 120-230V AC
Rated Current: 5-480A

Product Description

SIEMENS 3RW3017-1BB14 SIRIUS SOFT STARTER S00 12.5 A, 5.5 KW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC SCREW TERMINALS

The **SIEMENS 3RW3017-1BB14 SIRIUS SOFT STARTER S00** is a motor control device intended for industrial applications. This soft starter is rated for 12.5 A, 5.5 kW at 400 V, and is suitable for operation at temperatures up to 40°C. It is compatible with input voltages ranging from 200 V to 480 V AC and 110-230 V AC/DC with screw terminals for connections. Soft starters like the SIRIUS S00 are utilized to govern the starting and stopping of electric motors, lessening the stress on the motor during startup and providing a smoother acceleration process. They are commonly employed in various industrial settings to enhance motor performance and efficiency.

| Product | |
|--------------------------------|--|
| Article Number | 3RW3017-1BB14 |
| Product Description | SIRIUS soft starter S00 12.5 A, 5.5 kW/400 V, 40 °C 200-480 V |
| | AC, 110-230 V AC/DC Screw terminals |
| Product family | 3RW30 soft starters |
| Product Lifecycle (PLM) | PM300:Active Product |
| Price data | |
| Price Group | 42G |
| List Price | Show prices |
| Customer Price | Show prices |
| Surcharge for Raw | see also metal factor (further details are available on the help |
| Material | page) |
| Metal Factor | LBO |
| Delivery information | |
| Export Control | AL:N/ECCN:N |
| Regulations | |
| Estimated dispatch time | 3 Day(s) |
| (Working Days) | |
| Net Weight (kg) | 0,439 Kg |
| Packaging Dimension | 210,00 x 163,00 x 60,00 |
| Package size unit of | MM |
| measure | |
| Quantity Unit | 1 Piece |
| Packaging Quantity | 1 |
| Additional Product Information | |
| EAN | 4011209719644 |
| UPC | 754554958330 |
| Commodity Code | 85371098 |
| LKZ_FDB/ CatalogID | CC-IC10 |
| Product Group | 5345 |
| Group Code | R711 |
| Country of origin | Czech Republic |





VOBOAL Shenzhen Voboal Industrial Automation Co., Ltd.

+8613760462017

sale@voboal.com

plcsimatic.com

 $Sienteng\ Zhongbao\ Industrial\ Park, Longdong\ Community,\ Baolong\ Street,\ Longgang\ District,\ Shenzhen$