

SIEMENS 6ES7322-1BH81-0AA0 SIMATIC S7-300, DIGITAL OUTPUT SM 322, OPTICALLY ISOLATED, FOR EXPANDED TEMPERATURE RANGE

Our Product Introduction

Basic Information

- Place of Origin: Germany
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 6ES7322-1BH81-0AA0
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: Not available
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100



Product Specification

- Touchscreen: Yes
- Communication Interface: PROFINET, PROFIBUS DP
- Processor: ARM Cortex A8
- Mounting Options: Panel Or VESA Mount
- Weight: Standard: 0.8 Kg, Compact: 0.5 Kg
- Number Of Digital Outputs: 4/8/16/32/40/48/64/80/96/120/128/144/160/192/256
- Number Of Analog Outputs: 2/4/8/12/16
- Data Memory: 256 KB
- Operating System: Windows Embedded Compact Or Linux
- Number Of Timers: 4/8/16/32
- Memory Size: 256 KB To 2 MB
- Cpu Type: S7-300
- Mounting Type: Panel Mounting
- Number Of Digital Inputs: 8/16/24/32/40/48/64/80/96/120/128/144/160/192/256
- Communication Interfaces: PROFIBUS DP/MPI/PROFINET

Product Description

SIEMENS 6ES7322-1BH81-0AA0 SIMATIC S7-300, DIGITAL OUTPUT SM 322, OPTICALLY ISOLATED, FOR EXPANDED TEMPERATURE RANGE

The **SIEMENS 6ES7322-1BH81-0AA0 SIMATIC S7-300 SM322** module is a Digital Output module designed for the SIMATIC S7-300 series. This module, SM322, features optically isolated digital outputs, providing enhanced protection against electrical noise and interference. Additionally, it is designed to operate within an expanded temperature range, ensuring reliability in environments with varying temperatures.

Digital Output modules like the SM322 with optical isolation are essential components in industrial automation systems, enabling the control system to send digital signals to external devices reliably. The optically isolated design enhances signal integrity and protection, critical for stable operation in industrial environments where noise and interference are common.

Product	
Article Number	6ES7322-1BH81-0AA0
Product Description	SIMATIC S7-300, DIGITAL OUTPUT SM 322, OPTICALLY ISOLATED, FOR EXPANDED TEMPERATURE RANGE, 16 DO, 24V DC, 0.5 A, 20 PIN
Product family	Not available
Product Lifecycle (PLM)	PM500:Discontinued Product or end of PLM & Support
PLM Effective Date	End of product lifecycle since: 01.10.2006
Notes	Product is no longer available. Successor: 6AG1322-1BH01-2AA0 Compare Products
Successor information	
Successor	6AG1322-1BH01-2AA0
Successor Description	SIPLUS S7-300 SM 322-20-pole based on 6ES7322-1BH01-0AA0 with conformal coating, -25...+70 °C, digital output isolated 16 DQ, 24 V DC, 0.5 A, total current 4 A/group (8 A/module)
Price data	
Price Group	2Z3
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	see also metal factor (further details are available on the help page)
Delivery information	
Export Control Regulations	ECCN : N / AL : N
Estimated dispatch time (Working Days)	1 Day(s)
Net Weight (kg)	0,240 Kg
Package size unit of measure	Not available
Quantity Unit	0 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4025515060925
UPC	Not available
Commodity Code	85389091
LKZ_FDB/CatalogID	ST9-E5
Product Group	2288
Group Code	R111
Country of origin	Germany



Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen