

SIEMENS 3RW4026-1BB14 SIRIUS SOFT STARTER S0 25 A, 11 KW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC SCREW TERMINALS

Our Product Introduction

Basic Information

- Place of Origin: Czech Republic
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 3RW4026-1BB14
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 210,00 x 182,00 x 58,00MM
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100



Product Specification

- Voltage: Up To 690V
- Motor Power Range: 1.5-560 KW
- Product Type: Soft Starter
- Protection Class: IP20, IP55
- Input Voltage: 120-230V AC
- Operating Temperature: -25 To 70°C
- Rated Voltage: 200-690V
- Communication Interfaces: PROFIBUS, PROFINET, Modbus RTU, Ethernet
- Enclosure Rating: IP20
- Current Range: 3-1050A
- Soft Stop: Ramp-down Time
- Soft Start Time: 0.1-20 Seconds
- Programming Software: SIRIUS Soft Starter ES
- Starting Modes: Soft Start/Soft Stop/Ramp Start

Product Description

SIEMENS 3RW4026-1BB14 SIRIUS SOFT STARTER S0 25 A, 11 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC SCREW TERMINALS

The ****SIEMENS 3RW4026-1BB14 SIRIUS Soft Starter S0**** is a reliable soft starter designed for industrial motor control applications. Here are the key specifications for this soft starter:

- ****Model:**** 3RW4026-1BB14
- ****Series:**** SIRIUS
- ****Soft Starter Type:**** S0
- ****Rated Current:**** 25A
- ****Rated Power at 400V:**** 11 kW
- ****Operational Temperature:**** Up to 40°C
- ****Voltage Range:**** 200-480V AC
- ****Control Voltage:**** 110-230V AC/DC
- ****Terminal Type:**** Screw Terminals

This soft starter is suitable for controlling motors up to 11 kW at 400V. With screw terminals for easy and secure wiring connections, it provides reliable motor control in various industrial environments, ensuring smooth motor startup and reducing mechanical stress on the system.

Product	
Article Number	3RW4026-1BB14
Product Description	SIRIUS soft starter S0 25 A, 11 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC Screw terminals
Product family	3RW40 soft starters
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	42G
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	LAO-----
Delivery information	
Export Control Regulations	AL : N / ECCN : EAR99
Estimated dispatch time (Working Days)	3 Day(s)
Net Weight (kg)	0,696 Kg
Packaging Dimension	210,00 x 182,00 x 58,00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4011209691667
UPC	Not available
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	3727
Group Code	R711
Country of origin	Czech Republic



Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen