

SIEMENS 3RW4026-1BB15 SIRIUS SOFT STARTER S0 25 A, 15 KW/500 V, 40 °C 400-600 V AC, 110-230 V AC/DC SCREW TERMINALS

Basic Information

- Place of Origin: Czech Republic
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 3RW4026-1BB15
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 156,00 x 182,00 x 58,00MM
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100



Product Specification

- Soft Stop: Ramp-down Time
- Voltage Range: 200 V - 690 V
- Programming Options: Keypad, PC Software
- Rated Power: 1.5-560 KW
- Voltage: Up To 690V
- Communication Protocols: Modbus TCP, Ethernet/IP, DeviceNet
- Ambient Temperature Range: -25°C To +60°C
- Starting Torque: Adjustable
- Output Current: 5A
- Control Voltage: 24 V - 500 V AC/DC
- Programming Software: SIRIUS Soft Starter ES
- Certifications: CE, UL, CSA, CCC, GOST
- Communication Interface: Modbus RTU
- Application: Pumps, Fans, Compressors, Conveyors, Milling Machines, Crushers, Blenders

Product Description

SIEMENS 3RW4026-1BB15 SIRIUS SOFT STARTER S0 25 A, 15 kW/500 V, 40 °C 400-600 V AC, 110-230 V AC/DC SCREW TERMINALS

The ****SIEMENS 3RW4026-1BB15 SIRIUS Soft Starter S0**** is a robust soft starter designed for industrial motor control applications. Here are the key specifications for this soft starter:

- ****Model:**** 3RW4026-1BB15
- ****Series:**** SIRIUS
- ****Soft Starter Type:**** S0
- ****Rated Current:**** 25A
- ****Rated Power at 500V:**** 15 kW
- ****Operational Temperature:**** Up to 40°C
- ****Voltage Range:**** 400-600V AC
- ****Control Voltage:**** 110-230V AC/DC
- ****Terminal Type:**** Screw Terminals

This soft starter is capable of effectively controlling motors up to 15 kW at 500V. With screw terminals for easy and secure wiring connections, it provides reliable motor control in various industrial applications, ensuring smooth motor startup and reducing mechanical stress on the system.

Product	
Article Number	3RW4026-1BB15
Product Description	SIRIUS soft starter S0 25 A, 15 kW/500 V, 40 °C 400-600 V AC, 110-230 V AC/DC Screw terminals
Product family	3RW40 soft starters
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	42G
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	LAO-----
Delivery information	
Export Control Regulations	AL : N / ECCN : EAR99
Estimated dispatch time (Working Days)	5 Day(s)
Net Weight (kg)	0,696 Kg
Packaging Dimension	156,00 x 182,00 x 58,00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4011209691698
UPC	754554958828
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	3727
Group Code	R711
Country of origin	Czech Republic



Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen