

SIEMENS 3RW4026-2BB04 SIRIUS SOFT STARTER S0 25 A, 11 KW/400 V, 40 °C 200-480 V AC, 24 V AC/DC SPRING-TYPE TERMINALS

Basic Information

- Place of Origin: Czech Republic
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 3RW4026-2BB04
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 57,00 x 153,00 x 182,00MM
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100



Product Specification

- Braking Torque: Adjustable
- Fault Memory: Last 10 Faults Stored
- Overload Protection: Thermal Overload Relay
- Power Range: 3-250kW
- Communication Protocols: Modbus TCP, Ethernet/IP, DeviceNet
- Integrated Motor Protection: Available
- Rated Motor Power: 1.5-560 KW
- Ambient Temperature Range: -25°C To +60°C
- Efficiency: 90%
- Programming: Multi-language
- Rated Power: 1.5-560 KW
- Starting Time: Adjustable
- Ramp-Up Time: 0-30 Seconds
- Rated Voltage: 200-690V

Product Description

SIEMENS 3RW4026-2BB04 SIRIUS SOFT STARTER S0 25 A, 11 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC SPRING-TYPE TERMINALS

The ****SIEMENS 3RW4026-2BB04 SIRIUS Soft Starter S0**** is a reliable soft starter designed for industrial motor control applications. Here are the key specifications for this soft starter:

- ****Model:**** 3RW4026-2BB04
- ****Series:**** SIRIUS
- ****Soft Starter Type:**** S0
- ****Rated Current:**** 25A
- ****Rated Power at 400V:**** 11 kW
- ****Operational Temperature:**** Up to 40°C
- ****Voltage Range:**** 200-480V AC
- ****Control Voltage:**** 24V AC/DC
- ****Terminal Type:**** Spring-type Terminals

This soft starter is capable of efficiently controlling motors up to 11 kW at 400V. With spring-type terminals for convenient and secure wiring connections, it provides reliable and precise motor control in various industrial environments, ensuring smooth acceleration and deceleration of motors while reducing mechanical stress and power surges.

Product	
Article Number	3RW4026-2BB04
Product Description	SIRIUS soft starter S0 25 A, 11 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC spring-type terminals
Product family	3RW40 soft starters
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	42G
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	LAO-----
Delivery information	
Export Control Regulations	AL : N / ECCN : EAR99
Estimated dispatch time (Working Days)	3 Day(s)
Net Weight (kg)	0,751 Kg
Packaging Dimension	57,00 x 153,00 x 182,00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4011209694040
UPC	754554958668
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	3727
Group Code	R711
Country of origin	Czech Republic

