

SIEMENS 3RW4026-2BB15 SIRIUS SOFT STARTER S0 25 A, 15 KW/500 V, 40 °C 400-600 V AC, 110-230 V AC/DC SPRING-TYPE

Basic Information

- Place of Origin: Czech Republic
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 3RW4026-2BB15
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 154,00 x 59,00 x 182,00MM
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100



Product Specification

- Parameter Copying: Yes
- Weight: Depends On Model
- Motor Power Range: 1.5-560 KW
- Braking Torque: Adjustable
- Protection Rating: IP20
- Output Voltage: 24V DC
- Installation: DIN Rail Or Panel Mounting
- Dimensions: 154,00 X 59,00 X 182,00mm
- Communication: PROFIBUS, PROFINET, Modbus RTU
- Current Range: 3-1050 A
- Protection Class: IP20, IP55
- Soft Stop Time: 0.1-20 Seconds
- Rated Power: 1.5-560 KW
- Voltage Range: 200-690 V
- Programming: Multi-language

Product Description

SIEMENS 3RW4026-2BB15 SIRIUS SOFT STARTER S0 25 A, 15 kW/500 V, 40 °C 400-600 V AC, 110-230 V AC/DC SPRING-TYPE

The **SIEMENS 3RW4026-2BB15 SIRIUS SOFT STARTER S0** is a soft starter device with the following specifications:

- **Model:** 3RW4026-2BB15
- **Product Name:** SIRIUS SOFT STARTER S0
- **Rated Current:** 25A
- **Rated Power:** 15 kW at 500V, 40°C
- **Input Voltage Range:**
 - 400-600V AC
 - 110-230V AC/DC
- **Connection Type:** Spring-type

This soft starter is designed to smoothly start and control the acceleration of electric motors. It can handle a rated current of 25A and a power of 15 kW at 500V and 40°C. The input voltage range is between 400-600V AC and 110-230V AC/DC, and it features a spring-type connection for easy installation.

Product	
Article Number	3RW4026-2BB15
Product Description	SIRIUS soft starter S0 25 A, 15 kW/500 V, 40 °C 400-600 V AC, 110-230 V AC/DC spring-type terminals
Product family	3RW40 soft starters
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	42G
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	LAO-----
Delivery information	
Export Control Regulations	AL : N / ECCN : EAR99
Estimated dispatch time (Working Days)	5 Day(s)
Net Weight (kg)	0,742 Kg
Packaging Dimension	154,00 x 59,00 x 182,00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4011209694897
UPC	754554958996
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	3727
Group Code	R711
Country of origin	Czech Republic



Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen