

# SIEMENS 3RW4027-1BB04 SIRIUS SOFT STARTER S0 32 A, 15 KW/400 V, 40 °C 200-480 V AC, 24 V AC/DC SCREW TERMINALS

## Basic Information

- Place of Origin: Czech Republic
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 3RW4027-1BB04
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 210,00 x 182,00 x 58,00MM
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100



## Product Specification

- Motor Connection: Direct Or Star-Delta
- Protection Class: IP20
- Protection Degree: IP20
- Stopping Torque: Adjustable
- Rated Operational Current: 3-105 A
- Integrated Pump Control: Yes
- Ambient Temperature: -10 To 50 Degrees Celsius
- Communication Interfaces: PROFIBUS, PROFINET, Modbus RTU, Ethernet
- Installation: DIN Rail Or Panel Mounting
- Cooling Method: Natural Convection
- Output Voltage: 24V DC
- Soft Start: Ramp-up Time
- Starting Method: Soft Start
- Motor Protection: Thermal Overload Relay

## Product Description

SIEMENS 3RW4027-1BB04 SIRIUS SOFT STARTER S0 32 A, 15 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC SCREW TERMINALS

The \*\*SIEMENS 3RW4027-1BB04 SIRIUS SOFT STARTER S0\*\* is a soft starter device with the following specifications:

- \*\*Model:\*\* 3RW4027-1BB04
- \*\*Product Name:\*\* SIRIUS SOFT STARTER S0
- \*\*Rated Current:\*\* 32A
- \*\*Rated Power:\*\* 15 kW at 400V, 40°C
- \*\*Input Voltage Range:\*\*
  - 200-480V AC
  - 24V AC/DC
- \*\*Connection Type:\*\* Screw terminals

This soft starter is designed to facilitate the smooth starting and control of the acceleration of electric motors. It can handle a rated current of 32A and a power of 15 kW at 400V and 40°C. The input voltage range is between 200-480V AC and 24V AC/DC, and it features screw terminals for secure and reliable connections.

Product	
Article Number	3RW4027-1BB04
Product Description	SIRIUS soft starter S0 32 A, 15 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC Screw terminals
Product family	<a href="#">3RW40 soft starters</a>
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	42G
List Price	<a href="#">Show prices</a>
Customer Price	<a href="#">Show prices</a>
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	LAO-----
Delivery information	
Export Control Regulations	AL : N / ECCN : EAR99
Estimated dispatch time (Working Days)	3 Day(s)
Net Weight (kg)	0,716 Kg
Packaging Dimension	210,00 x 182,00 x 58,00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4011209691704
UPC	754554958583
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	3727
Group Code	R711
Country of origin	Czech Republic



Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen