



SIEMENS 3RW4027-1BB14 SIRIUS SOFT STARTER S0 32 A, 15 KW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC SCREW TERMINALS

Our Product Introduction

Basic Information

- Place of Origin: Czech Republic
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 3RW4027-1BB14
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 155,00 x 181,00 x 58,00MM
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100



Product Specification

- Efficiency: 90%
- Voltage Range: 200-690 V
- Ambient Temperature Range: -10°C To +40°C
- Overload Protection: Class 10, 20 Or 30
- Energy Saving Function: Yes
- Software Tools: SIRIUS Soft Starter ES V15.1 Or Higher
- Soft Stop: Ramp-down Time
- Motor Voltage Ramp: Linear Or S-curve
- Starting Modes: Soft Start, Kick Start, Pump Start, Current Limit Start
- Mounting Type: DIN Rail
- Motor Control: Voltage Ramp Control, Current Ramp Control
- Power Range: 3-250 KW
- Protection Class: IP20, IP54, IP66

Product Description

SIEMENS 3RW4027-1BB14 SIRIUS SOFT STARTER S0 32 A, 15 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC SCREW TERMINALS

The **SIEMENS 3RW4027-1BB14 SIRIUS SOFT STARTER S0** is a soft starter device with the following specifications:

- **Model:** 3RW4027-1BB14
- **Product Name:** SIRIUS SOFT STARTER S0
- **Rated Current:** 32A
- **Rated Power:** 15 kW at 400V, 40°C
- **Input Voltage Range:**
 - 200-480V AC
 - 110-230V AC/DC
- **Connection Type:** Screw terminals

This soft starter is designed to facilitate the smooth starting and control of the acceleration of electric motors. It can handle a rated current of 32A and a power of 15 kW at 400V and 40°C. The input voltage range is between 200-480V AC and 110-230V AC/DC, and it features screw terminals for secure and reliable connections.

Product	
Article Number	3RW4027-1BB14
Product Description	SIRIUS soft starter S0 32 A, 15 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC Screw terminals
Product family	3RW40 soft starters
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	42G
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	LAO-----
Delivery information	
Export Control Regulations	AL : N / ECCN : EAR99
Estimated dispatch time (Working Days)	3 Day(s)
Net Weight (kg)	0,705 Kg
Packaging Dimension	155,00 x 181,00 x 58,00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4011209691728
UPC	Not available
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	3727
Group Code	R711
Country of origin	Czech Republic



Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen