SIEMENS 3RW4027-1BB15 SIRIUS SOFT STARTER S0 32 A, 18.5 K KW/500 V, 40 °C 400-600 V AC, 110-230 V AC/DC SCREW TERMINALS

Basic Information

Place of Origin: Czech Republic
 Brand Name: SIEMENS
 Certification: CE

Model Number: 3RW4027-1BB15

Minimum Order Quantity: 1Price: USD

• Packaging Details: 210,00 x 183,00 x 60,00MM

Delivery Time: 10-12Days
Payment Terms: L/C, T/T
Supply Ability: 100



Product Specification

• Stop Function: Coast To Stop

Programming Software: SIRIUS Soft Starter ES

• Communication Interfaces: PROFIBUS, PROFINET, Modbus RTU,

Ethernet/IP

• Starting Modes: Current Limit, Voltage Ramp, Kick Start

Enclosure Rating: IP20, IP55, IP66
 Motor Connection: Direct Or Star-Delta

Energy Saving Function: Yes

• Soft Start Function: Ramp-up, Kickstart, Pump Control

• Weight: Depends On Model

• Protection Degree: IP20

Motor Protection: Thermal Overload Relay

Motor Control: Soft Start, Soft Stop, Pump Control

Input Voltage: 120-230V ACVoltage: Up To 690V

Product Description

SIEMENS 3RW4027-1BB15 SIRIUS SOFT STARTER S0 32 A, 18.5 K KW/500 V, 40 °C 400-600 V AC, 110-230 V AC/DC **SCREW TERMINALS**

The **SIEMENS 3RW4027-1BB15 SIRIUS SOFT STARTER S0** is a soft starter device with the following specifications:

- **Model:** 3RW4027-1BB15
- **Product Name:** SIRIUS SOFT STARTER S0 **Rated Current:** 32A
- **Rated Power:** 18.5 kW at 500V, 40°C
- **Input Voltage Range:**
- 400-600V AC
- 110-230V AC/DC
- **Connection Type:** Screw terminals

This soft starter is designed to facilitate the smooth starting and control of the acceleration of electric motors. It can handle a rated current of 32A and a power of 18.5 kW at 500V and 40°C. The input voltage range is between 400-600V AC and 110-230V AC/DC, and it features screw terminals for secure and reliable connections.

Product	
Article Number	3RW4027-1BB15
Atticle Number	SIRIUS soft starter S0 32 A, 18.5 k kW/500 V, 40 °C 400-600 V
Product Description	AC, 110-230 V AC/DC Screw terminals
Product family	3RW40 soft starters
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	42G
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw	see also metal factor (further details are available on the help
Material	page)
Metal Factor	LAO
Delivery information	
Export Control	AL:N/ECCN:EAR99
Regulations	
Estimated dispatch time	5 Day(s)
(Working Days)	
Net Weight (kg)	0,719 Kg
Packaging Dimension	210,00 x 183,00 x 60,00
Package size unit of	MM
measure	
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4011209691759
UPC	754554958835
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	3727
Group Code	R711
Country of origin	Czech Republic





VOBOAL Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

 $Sienteng\ Zhongbao\ Industrial\ Park, Longdong\ Community,\ Baolong\ Street,\ Longgang\ District,\ Shenzhen$