

SIEMENS 3RW4028-1BB04 SIRIUS SOFT STARTER S0 38 A, 18.5 KW/400 V, 40 °C 200-480 V AC, 24 V AC/DC SCREW TERMINALS

Our Product Introduction

Basic Information

- Place of Origin: Czech Republic
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 3RW4028-1BB04
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 154,00 x 181,00 x 60,00MM
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100



Product Specification

- Energy Saving Function: Yes
- Protection Rating: IP20
- Motor Control: Soft Stop, Soft Start, Pump Control
- Soft Start Time: 0-20 Seconds
- Fault Memory: Last 10 Faults Stored
- Operating Temperature: -25°C To +60°C
- Communication Interfaces: Profibus/Profinet/Ethernet/IP/Modbus RTU
- Starting Modes: Soft Start/Soft Stop/Ramp Start
- Motor Connection: Direct Or Star-Delta
- Ramp-Down Time: 0-20 Seconds
- Stop Function: Coast To Stop
- Communication Interface: PROFIBUS, PROFINET, Modbus RTU, Ethernet
- Enclosure Material: Plastic, Metal
- Rated Operational Voltage: Up To 690V

for more products please visit us on plcsimatic.com

Product Description

SIEMENS 3RW4028-1BB04 SIRIUS SOFT STARTER S0 38 A, 18.5 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC SCREW TERMINALS

The **SIEMENS 3RW4028-1BB04 SIRIUS SOFT STARTER S0** is a soft starter device with the following specifications:


- **Model:** 3RW4028-1BB04
- **Product Name:** SIRIUS SOFT STARTER S0
- **Rated Current:** 38A
- **Rated Power:** 18.5 kW at 400V, 40°C
- **Input Voltage Range:**
 - 200-480V AC
 - 24V AC/DC
- **Connection Type:** Screw terminals

This soft starter is designed to facilitate the smooth starting and control of the acceleration of electric motors. It can handle a rated current of 38A and a power of 18.5 kW at 400V and 40°C. The input voltage range is between 200-480V AC and 24V AC/DC, and it features screw terminals for secure and reliable connections.

Product	
Article Number	3RW4028-1BB04
Product Description	SIRIUS soft starter S0 38 A, 18.5 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC Screw terminals
Product family	3RW40 soft starters
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	42G
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	LAO-----
Delivery information	
Export Control Regulations	AL : N / ECCN : EAR99
Estimated dispatch time (Working Days)	3 Day(s)
Net Weight (kg)	0,714 Kg
Packaging Dimension	154,00 x 181,00 x 60,00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4011209691766
UPC	040892691948
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	3727
Group Code	R711
Country of origin	Czech Republic

WARNING!
HAZARDOUS VOLTAGE. CAN CAUSE
ELECTRICAL SHOCK AND BURNS.
DISCONNECT POWER BEFORE
PROCEEDING WITH ANY WORK ON THIS
EQUIPMENT AND OBSERVE THE
OPERATING INSTRUCTIONS.

ADVERTENCIA!
¡TENSIÓN PELIGROSA! PUEDE CAUSAR
CHOQUE ELÉCTRICO Y QUEMADURAS.
ANTES DE COMENZAR LOS TRABAJOS
DESCONECTAR Y AISLAR DE ALIMENTACIÓN
LA INSTALACIÓN Y EL EQUIPO, Y RESPETAR
LO INDICADO EN LAS INSTRUCCIONES.




<http://support.industry.siemens.com>

SIEMENS


Sanftstarter, soft starter
démarrreur progressif
arrancador suave, dispos. d. partida suave
пускатель перем. тока
交流半导体电动机起动器

1P 3RW4028-1BB04
S 1P3RW4028-1BB04+SL
3BA 18,5kW 400V 40°C
200-480V/US 24V
GB/T14048.6

AVISO!
TENSÃO ELÉTRICA PERIGOSA! PODE
CAUSAR UM CHOQUE ELÉTRICO E
QUEIMADURAS. ANTES DE INICIAR OS
TRABALHOS, DESLIGUE A TENSÃO DA
UNIDADE E DO APARELHO E
CONSULTAR, ADICIONALMENTE,
O MANUAL DE SERVIÇO.



LO QTY: 1
230213 *E08*
S2D



Mfr.: Siemens AG, DE-92220 Amberg
捷克制造 Сделано в Чехии

Made in Czech Rep.
Hecho en Rep. Checa



Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen