

## SIEMENS 3RW4028-1BB15 SIRIUS SOFT STARTER S0 38 A, 22 KW/500 V, 40 °C 400-600 V AC, 110-230 V AC/DC SCREW TERMINALS

### Basic Information

- Place of Origin: Czech Republic
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 3RW4028-1BB15
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 210.00 x 181.00 x 58.00MM
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100



### Product Specification

- Ambient Temperature Range: -10°C To +40°C
- Power Range: 1.1-560kW
- Model: 3RW Soft Starters
- Motor Load Monitoring: Yes
- Stop Function: Coast To Stop
- Starting Voltage: Adjustable From 20-100%
- Motor Connection: Direct Or Star-Delta
- Protection Class: IP20, IP55
- Starting Time: 0-30 Seconds
- Built-In Functions: Energy Saving, Pump Cleaning, Motor Protection, Motor Brake Control
- Motor Control Modes: Soft Start, Soft Stop, Kick Start, Pump Control, Torque Control
- Display: LCD With Backlight
- Protection Features: Overload, Underload, Phase Loss, Phase

## Product Description

SIEMENS 3RW4028-1BB15 SIRIUS SOFT STARTER S0 38 A, 22 kW/500 V, 40 °C 400-600 V AC, 110-230 V AC/DC SCREW TERMINALS

The \*\*SIEMENS 3RW4028-1BB15 SIRIUS SOFT STARTER S0\*\* is a soft starter device with the following specifications:

- \*\*Model:\*\* 3RW4028-1BB15
- \*\*Product Name:\*\* SIRIUS SOFT STARTER S0
- \*\*Rated Current:\*\* 38A
- \*\*Rated Power:\*\* 22 kW at 500V, 40°C
- \*\*Input Voltage Range:\*\*
  - 400-600V AC
  - 110-230V AC/DC
- \*\*Connection Type:\*\* Screw terminals

This soft starter is designed to facilitate the smooth starting and control of the acceleration of electric motors. It can handle a rated current of 38A and a power of 22 kW at 500V and 40°C. The input voltage range is between 400-600V AC and 110-230V AC/DC, and it features screw terminals for secure and reliable connections.

Product	
Article Number	3RW4028-1BB15
Product Description	SIRIUS soft starter S0 38 A, 22 kW/500 V, 40 °C 400-600 V AC, 110-230 V AC/DC Screw terminals
Product family	<a href="#">3RW40 soft starters</a>
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group / Headquarter Price Group	42G / 42G
List Price	<a href="#">Show prices</a>
Customer Price	<a href="#">Show prices</a>
Metal Factor	LAO-----
Delivery information	
Export Control Regulations	AL : N / ECCN : EAR99
Estimated dispatch time (Working Days)	5 Day(s)
Net Weight (kg)	0.705 Kg
Packaging Dimension	210.00 x 181.00 x 58.00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4011209691810
UPC	754554958842
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	3727
Group Code	R711
Country of origin	Czech Republic


WARNING!  
HAZARDOUS VOLTAGE. CAN CAUSE  
ELECTRICAL SHOCK AND BURNS.  
DISCONNECT POWER BEFORE  
PROCEEDING WITH ANY WORK ON THIS  
EQUIPMENT AND OBSERVE THE  
OPERATING INSTRUCTIONS.

ADVERTENCIA!  
¡TENSIÓN PELIGROSA! PUEDE CAUSAR  
CHOQUE ELÉCTRICO Y QUEMADURAS.  
ANTES DE COMENZAR LOS TRABAJOS,  
DESCONECTAR Y AISLAR DE ALIMENTACIÓN  
LA INSTALACIÓN Y EL EQUIPO, Y RESPETAR  
LO INDICADO EN LAS INSTRUCCIONES.

AVISO!  
TENSÃO ELÉTRICA PERIGOSA! PODE  
CAUSAR UM CHOQUE ELÉTRICO E  
QUEIMADURAS. ANTES DE INICIAR OS  
TRABALHOS, DESLIGUE A TENSÃO DA  
UNIDADE E DO APARELHO E  
CONSULTAR, ADICIONALMENTE,  
O MANUAL DE SERVIÇO.

UK  
CA

Importer:  
Siemens plc,  
Manchester M20 2UR, UK



<http://support.siemens.com>

CCC EAC CE




**SIEMENS**

Sanftstarter, soft starter  
démarrreur progressif  
arrancador suave, dispos. d. partida suave  
плавный пускатель  
交流半导体电动机起动器

1P 3RW4028-1BB15  
S 1P3RW4028-1BB15-SL0231120  
38A 22kW 500V 40°C  
400-600V/US 110-230V  
GB/T14048.6

LO QTY: 1  
231120 \*E08\*  
S01



Mfr.: Siemens AG, DE-92220 Amberg  
德克制造 Сделано в Чехии

Made in Czech Rep.  
Hecho en Rep. Checa



Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen