

## SIEMENS 3RW4036-1BB14 SIRIUS soft starter S2 45 A, 22 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC Screw terminals

### Basic Information

- Place of Origin: Czech Republic
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 3RW4036-1BB14
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 215,00 x 198,00 x 71,00MM
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100



### Product Specification

- Integrated Bypass: Yes
- Overload Protection: Thermal Overload Relay
- Starting Method: Soft Start
- Dimensions: 215,00 X 198,00 X 71,00 Mm
- Mounting Options: DIN Rail / Panel Mount
- Programming Software: SIRIUS Soft Starter ES
- Current Limiting: Yes
- Power Rating: Up To 250 KW
- Rated Voltage: 200-690V
- Stopping Torque: Adjustable
- Programming Options: Keypad, PC Software
- Efficiency: 90%
- Installation: DIN Rail Or Panel Mounting
- Warranty: 2 Years

## Product Description

SIEMENS 3RW4036-1BB14 SIRIUS SOFT STARTER S2 45 A, 22 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC SCREW TERMINALS

The \*\*SIEMENS 3RW4036-1BB14 SIRIUS Soft Starter S2\*\* specifications are as follows:

- \*\*Model:\*\* 3RW4036-1BB14
- \*\*Product Type:\*\* SIRIUS Soft Starter S2
- \*\*Rated Operational Current:\*\* 45 A
- \*\*Rated Operational Power at 400 V:\*\* 22 kW
- \*\*Operating Temperature:\*\* Up to 40 °C
- \*\*Input Voltage:\*\* 200-480 V AC
- \*\*Control Voltage:\*\* 110-230 V AC/DC
- \*\*Terminal Type:\*\* Screw Terminals

This soft starter is designed to handle a maximum operational current of 45 A and a power rating of 22 kW at 400 V. It can operate in temperatures up to 40 °C and accepts an input voltage range of 200-480 V AC. The control voltage required for this unit is in the range of 110-230 V AC/DC, and it is designed with screw terminals for secure and reliable connections in industrial setups.

Product	
Article Number	3RW4036-1BB14
Product Description	SIRIUS soft starter S2 45 A, 22 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC Screw terminals
Product family	<a href="#">3RW40 soft starters</a>
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	42G
List Price	<a href="#">Show prices</a>
Customer Price	<a href="#">Show prices</a>
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	LAO-----
Delivery information	
Export Control Regulations	AL : N / ECCN : EAR99
Estimated dispatch time (Working Days)	3 Day(s)
Net Weight (kg)	1,281 Kg
Packaging Dimension	215,00 x 198,00 x 71,00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4011209691841
UPC	Not available
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	3727
Group Code	R711
Country of origin	Czech Republic

