

SIEMENS 3RW4037-1BB14 SIRIUS SOFT STARTER S2 63 A, 30 KW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC SCREW TERMINALS

Basic Information

- Place of Origin: Czech Republic
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 3RW4037-1BB14
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 212,00 x 197,00 x 73,00CM
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100



Product Specification

- Additional Features: Overload And Short Circuit Protection
- Rated Operational Voltage: 200-690 V AC
- Control Modes: Current Limit, Torque Control, Voltage Ramp, Kick Start
- Current Limiting: Yes
- Motor Load Display: Yes
- Protection Class: IP20
- Motor Control: Soft Start, Soft Stop, Pump Control
- Efficiency: 90%
- Communication Interface: Modbus RTU
- Communication Interfaces: PROFIBUS, PROFINET, Modbus RTU, Ethernet/IP
- Software Tools: SIRIUS Soft Starter ES V15.1 Or Higher
- Braking Torque: Adjustable
- Programming: Via Keypad Or PC Software
- Starting Torque: Adjustable

Product Description

SIEMENS 3RW4037-1BB14 SIRIUS SOFT STARTER S2 63 A, 30 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC SCREW TERMINALS

The **SIEMENS 3RW4037-1BB14 SIRIUS Soft Starter** specifications are as follows:

- **Model:** 3RW4037-1BB14
- **Product Type:** SIRIUS Soft Starter
- **Rated Current:** 63 A
- **Rated Power (at 400 V):** 30 kW
- **Voltage Range:** 200-480 V AC
- **Control Voltage:** 110-230 V AC/DC
- **Terminal Type:** Screw Terminals
- **Operating Temperature:** Up to 40 °C

This soft starter from Siemens is designed to control the starting and stopping of electric motors, providing a gradual increase in voltage to reduce mechanical stress during startup. It is rated for a maximum current of 63 A and a power output of 30 kW at 400 V. The soft starter is compatible with voltage inputs ranging from 200 V to 480 V AC and operates with a control voltage of 110-230 V AC/DC. The terminals are of the screw type, facilitating easy and secure wiring connections. The device is designed to operate within a temperature range of up to 40 °C.

Product	
Article Number	3RW4037-1BB14
Product Description	SIRIUS soft starter S2 63 A, 30 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC Screw terminals
Product family	3RW40 soft starters
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	42G
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	LAO-----
Delivery information	
Export Control Regulations	AL : N / ECCN : EAR99
Estimated dispatch time (Working Days)	3 Day(s)
Net Weight (kg)	1,273 Kg
Packaging Dimension	212,00 x 197,00 x 73,00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4011209692077
UPC	Not available
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	3727
Group Code	R711
Country of origin	Czech Republic



VOBOAL Shenzhen Voboal Industrial Automation Co., Ltd.

+8613760462017

sale@voboal.com

plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen