

SIEMENS 3RW4037-2TB04 SIRIUS SOFT STARTER S2 63 A, 30 KW/400 V, 40 °C 200-480 V AC, 24 V AC/DC SPRING-TYPE

Our Product Introduction

Basic Information

- Place of Origin: Czech Republic
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 3RW4037-2TB04
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 68,00 x 170,00 x 198,00MM
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100



Product Specification

- Energy Saving Function: Yes
- Programming Options: Keypad, PC Software
- Integrated Pump Control: Yes
- Programming Software: SIRIUS Soft Starter ES
- Rated Operational Current: 0.37-560A
- Ambient Temperature: -10 To 50 Degrees Celsius
- Starting Torque: Adjustable
- Motor Protection: Thermal Overload Relay
- Rated Current: 5-480A
- Motor Load Display: Yes
- Starting Voltage: Adjustable From 20-100%
- Integrated Bypass: Yes
- Voltage Range: 200-690V
- Ramp Time: 0.1-60 Seconds
- Weight: 1,272 Kg

Product Description

SIEMENS 3RW4037-2TB04 SIRIUS SOFT STARTER S2 63 A, 30 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC SPRING-TYPE

The **SIEMENS 3RW4037-2TB04 SIRIUS Soft Starter** specifications are as follows:

- **Model:** 3RW4037-2TB04
- **Product Type:** SIRIUS Soft Starter
- **Rated Current:** 63 A
- **Rated Power (at 400 V):** 30 kW
- **Voltage Range:** 200-480 V AC
- **Control Voltage:** 24 V AC/DC
- **Terminal Type:** Spring-Type Terminals
- **Operating Temperature:** Up to 40 °C

This Siemens soft starter is designed for efficiently controlling the starting and stopping of electric motors. It has a rated current of 63 A and can handle a power output of 30 kW at 400 V. The soft starter is suitable for voltage inputs ranging from 200 V to 480 V AC and operates with a control voltage of 24 V AC/DC. Featuring spring-type terminals, it provides a secure and reliable connection mechanism. The device is designed to operate within a temperature range of up to 40 °C, making it suitable for various industrial applications.

Product	
Article Number	3RW4037-2TB04
Product Description	SIRIUS soft starter S2 63 A, 30 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC spring-type terminals Thermistor motor protection
Product family	3RW40 soft starters
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	42G
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	LAO-----
Delivery information	
Export Control Regulations	AL : N / ECCN : N
Estimated dispatch time (Working Days)	5 Day(s)
Net Weight (kg)	1,272 Kg
Packaging Dimension	68,00 x 170,00 x 198,00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4011209696358
UPC	Not available
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	3727
Group Code	R711
Country of origin	Czech Republic



Shenzhen Voboal Industrial Automation Co., Ltd.



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen