

## SIEMENS 3RW4038-1TB04 SIRIUS SOFT STARTER S2 72 A, 37 KW/400 V, 40 °C 200-480 V AC, 24 V AC/DC

### Basic Information

- Place of Origin: Czech Republic
- Brand Name: SIEMENS
- Certification: CE
- Model Number: 3RW4038-1TB04
- Minimum Order Quantity: 1
- Price: USD
- Packaging Details: 212,00 x 197,00 x 71,00MM
- Delivery Time: 10-12Days
- Payment Terms: L/C, T/T
- Supply Ability: 100



### Product Specification

- Communication: PROFIBUS, PROFINET, Modbus RTU
- Parameter Copying: Yes
- Mounting Options: DIN Rail / Panel Mount
- Programming Software: SIRIUS Soft Starter ES
- Stop Function: Coast To Stop
- Degree Of Protection: IP20
- Energy Saving Function: Yes
- Ambient Temperature: -10 To 50 Degrees Celsius
- Rated Current: 5-480A
- Output Voltage: 24V DC
- Communication Interface: PROFIBUS, PROFINET, Modbus
- Protection Rating: IP20
- Motor Voltage Ramp: Linear Or S-curve
- Rated Voltage: 200-690V
- Input Voltage: 120-230V AC

## Product Description

SIEMENS 3RW4038-1TB04 SIRIUS SOFT STARTER S2 72 A, 37 KW/400 V, 40 °C 200-480 V AC, 24 V AC/DC

The \*\*SIEMENS 3RW4038-1TB04 SIRIUS Soft Starter\*\* specifications are as follows:

- \*\*Model:\*\* 3RW4038-1TB04
- \*\*Product Type:\*\* SIRIUS Soft Starter
- \*\*Rated Current:\*\* 72 A
- \*\*Rated Power (at 400 V):\*\* 37 kW
- \*\*Voltage Range:\*\* 200-480 V AC
- \*\*Control Voltage:\*\* 24 V AC/DC
- \*\*Operating Temperature:\*\* Up to 40 °C

This Siemens soft starter is designed for efficiently controlling the starting and stopping of electric motors. It has a rated current of 72 A and can handle a power output of 37 kW at 400 V. The soft starter is compatible with voltage inputs ranging from 200 V to 480 V AC and operates with a control voltage of 24 V AC/DC. The device is designed to operate within a temperature range of up to 40 °C, making it suitable for various industrial applications where precise motor control is required.

Product	
Article Number	3RW4038-1BB15
Product Description	SIRIUS soft starter S2 72 A, 45 kW/500 V, 40 °C 400-600 V AC, 110-230 V AC/DC Screw terminals
Product family	<a href="#">3RW40 soft starters</a>
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	42G
List Price	<a href="#">Show prices</a>
Customer Price	<a href="#">Show prices</a>
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	LAO-----
Delivery information	
Export Control Regulations	AL : N / ECCN : N
Estimated dispatch time (Working Days)	5 Day(s)
Net Weight (kg)	1,291 Kg
Packaging Dimension	212,00 x 197,00 x 71,00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4011209693166
UPC	754554958866
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	3727
Group Code	R711
Country of origin	Czech Republic



**Shenzhen Voboal Industrial Automation Co., Ltd.**



+8613760462017



sale@voboal.com



plcsimatic.com

Sienteng Zhongbao Industrial Park, Longdong Community, Baolong Street, Longgang District, Shenzhen