Czech Republic SIEMENS

3RW5055-6AB15

232,00 x 556,00 x 186,00MM

CE

1

USD

10-12Days

L/C, T/T 100

SIEMENS 3RW5055-6AB15 SIRIUS SOFT STARTER 200-600 V 143 A, 110-250 V AC SCREW TERMINALS ANALOG OUTPUT

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

 Stopping Torque: 	Adjustable
 Protection Degree: 	IP20
Enclosure Material:	Plastic, Metal
Soft Stop Time:	0.1-20 Seconds
Stop Function:	Coast To Stop
 Motor Load Display: 	Yes
 Rated Frequency: 	50/60Hz
Rated Operational Voltage:	200-690V
 Programming Options: 	Keypad, PC Software
Output Current:	5A
 Starting Torque: 	Adjustable
 Fault Memory: 	Last 10 Faults Stored
 Programming Software: 	SIRIUS Soft Starter ES
Motor Protection:	Thermal Overload Relay, Electronic Overload Relay

Our Product Introduction

Product Description

SIEMENS 3RW5055-6AB15 SIRIUS SOFT STARTER 200-600 V 143 A, 110-250 V AC SCREW TERMINALS ANALOG OUTPUT

The **SIEMENS 3RW5055-6AB15** is a part of the **SIRIUS** soft starter series, designed for industrial applications to facilitate the controlled starting and stopping of motors. Here are the key specifications for this specific soft starter model: - **Product Code:** 3RW5055-6AB15 - **Product Line:** SIRIUS

- **Rated Voltage:** 200-600 V

- **Rated Current:** 143 A **Control Voltage:** 110-250 V AC **Terminal Type:** Screw terminals
- **Additional Feature:** Analog output

This soft starter is ideal for applications where precise motor control is necessary for efficient operation. The inclusion of an analog output feature provides additional monitoring and control capabilities within the system. The presence of screw terminals facilitates easy and secure wiring, making installation and maintenance processes more convenient. Product

Product	
Article Number	3RW5055-6AB15
Product Description	SIRIUS soft starter 200-600 V 143 A, 110-250 V AC Screw
	terminals Analog output
Product family	3RW50 soft starters
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	42S
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	LAO
Delivery information	
Export Control Regulations	AL : N / ECCN : N
Estimated dispatch time (Working Days)	3 Day(s)
Net Weight (kg)	4,000 Kg
Packaging Dimension	232,00 x 556,00 x 186,00
Package size unit of measure MM	
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4047621060262
UPC	Not available
Commodity Code	85371098
LKZ_FDB/ CatalogID	CC-IC10
Product Group	4980
Group Code	R711
Country of origin	Czech Republic

